

## HS 252 - STANDARD ASSEMBLY TORQUES

### TABLE OF CONTENTS

1	SCOPE .....	7
2	PURPOSE .....	7
3	DOCUMENT CONTROL .....	7
4	REFERENCES .....	7
5	WARNINGS .....	8
6	APPLICATIONS .....	8
6.1	APPLICATION NOTES .....	11
7	TORQUE TOLERANCES .....	11
8	LINK TO HS DOCUMENTS .....	11
9	HGT-80 STANDARD (SCREWS AND THREADED RODS - 80% PRELOAD) .....	12
10	HGT-50 STANDARD (SCREWS AND THREADED RODS - 50% PRELOAD) .....	13
11	HGT-35 STANDARD (SCREWS - 35% PRELOAD) .....	14
12	HGT-SS STANDARD (SET SCREWS) .....	15
13	HGT-LHCS STANDARD (LOW HEAD CAP SCREWS) .....	16
14	HGT-FT STANDARD (FITTINGS) .....	17
14.1	IMPORTANT NOTES .....	17
15	HGT-EL STANDARD (ELECTRICAL APPLICATIONS) .....	22
16	DRAWING SPECIFICATIONS .....	23
17	SUPPLIER RECOMMENDED TORQUE SPECIFICATIONS .....	25
17.1	HYDRAULIC MANIFOLDS – TORQUE VALUES FOR SCREWS .....	25
17.2	HYDRAULIC MANIFOLDS – TORQUE VALUES FOR ORIFICES .....	25
17.3	HOSE/PIPE CLAMPS – TORQUE VALUES FOR SCREWS .....	26
17.4	HYDRAULIC MOTORS – TORQUE FOR MOUNTING BOLTS .....	27
17.5	BOSCH REXROTH DBDS PRESSURE RELIEF VALVES .....	27
17.6	BLADDER ACCUMULATOR NECK ADAPTOR SPECIFICATIONS .....	28
17.7	HYDAC OIL LEVEL SIGHT GAUGE .....	28
17.8	HYDAC PRESSURE TRANSDUCERS .....	28
17.9	DANFOSS PRESSURE TRANSDUCER .....	28
17.10	NUMATICS AIR VALVE ASSEMBLY TORQUE SPECIFICATIONS .....	29
17.10.1	Torque Specifications for Numatics 2012 & 2035 Air Valve Assemblies .....	29
17.10.2	Torque Specifications for Numatics ISO 1, 2 & 3 Air Valve Assemblies .....	30

17.11	HYDAC MALE PRESSURE TEST POINT .....	31
18	INTERNATIONAL STANDARDS TORQUE SPECIFICATIONS .....	32
18.1	ISO 6162:1994 - SPLIT FLANGE ASSEMBLIES .....	32
18.2	CAUTION .....	32
18.3	NOTES .....	32
19	PET MOLD AND HOT RUNNER SPECIAL TORQUE SPECIFICATIONS .....	32
19.1	CAM FOLLOWER TORQUE SPECIFICATIONS .....	33
19.2	EOAT TUBE RETAINER PIN TORQUE SPECIFICATION.....	33
19.3	COOLPIK VACUUM/BLOW PIN TORQUE SPECIFICATIONS .....	33
19.4	COOLPIK MOVING PUCK INSTALLATION TORQUE SPECIFICATION .....	34
19.5	COOLPIK PLATE MOUNTING TORQUE SPECIFICATION.....	34
19.6	MOLD/HOT RUNNER LIFT BARS MOUNTING SCREWS TORQUE APPLICATIONS .....	35
19.7	GIB/WEAR PLATE MOUNTING SCREWS TORQUE SPECIFICATION .....	35
19.8	NECK RING PLUGS TORQUE SPECIFICATION.....	35
19.9	STACK INSERTS TORQUE SPECIFICATION .....	35
19.10	TORQUE SPECIFICATION FOR WATER MANIFOLDS TO SLIDES .....	36
19.11	TORQUE SPECIFICATION FOR SLIDE TO CONNECTING BARS .....	36
19.12	TORQUE SPECIFICATION FOR EOAT ASSY. TO ROBOT .....	36
19.13	TORQUE SPECIFICATION FOR NEXPET CORE SLEEVE SET SCREWS .....	36
20	APPENDIX.....	36
20.1	DLO DEVICE DETAILS (2205).....	37

## TABLE OF FIGURES

Figure 1 – Husky General Torque (HGT) - Standard Applications (# 1 to 8).....	9
Figure 2 – Using Hex Tool Adapter to Access Mold Mounting Screws .....	10
Figure 3 – Individual Torque Specifications .....	23
Figure 4 – Husky General Torque Chart.....	24
Figure 5 – Numatics 2012 & 2035 Air Valve Assemblies .....	29
Figure 6 – Numatics ISO 1, 2 & 3 Air Valve Assemblies .....	30
Figure 7 – EOAT Tube Retainer Pin Torque Specification.....	33
Figure 8 – Moving Puck Assembly Installation Torque Specification.....	34
Figure 9 – COOLPIK Assembly on Machine Plenum .....	34
Figure 10 – Torque Specification for NexPET Core Sleeve Set Screws .....	36

## TABLE OF TABLES

Table 1 – Husky General Torque (HGT) - Standard Applications .....	9
Table 2 – HGT-80 Metric Fasteners .....	12
Table 3 – HGT-80 Imperial Fasteners .....	12
Table 4 – HGT-50 Metric Fasteners .....	13
Table 5 – HGT-50 Imperial Fasteners .....	13
Table 6 – HGT-35 Metric Fasteners .....	14
Table 7 – HGT-35 Imperial Fasteners .....	14
Table 8 – HGT-SS Metric Set Screws .....	15
Table 9 – HGT-SS Imperial Screws .....	15
Table 10 – HGT-LHCS Metric Low Head Cap Screws .....	16
Table 11 – HGT-FT ORFS Tube Ends .....	18
Table 12 – HGT-FT ORFS Hose Ends (Manuli Hose Fittings) .....	18
Table 13 – HGT-FT SAE and BSPP Ends.....	19
Table 14 – HGT-FT JIC Ends.....	19
Table 15 – HGT-FT NPT and BSPT Plugs and Fittings .....	20
Table 16 – HGT-FT Flareless Tube Ends.....	20
Table 17 – HGT-FT SAE Plugs.....	20
Table 18 – HGT-FT Bulkhead Locknuts .....	20
Table 19 – HGT-FT BSPP Plugs .....	21
Table 20 – HGT-FT Metric Plugs.....	21
Table 21 – HGT-EL Metric and Imperial Screws, Mounting Hardware (Electrical Applications) .....	22
Table 22 – HGT-EL Heater Bands (Electrical Applications).....	22
Table 23 – HGT-EL Solid State Relays (Electrical Applications) .....	23
Table 24 – HGT-EL Premolded Cables (Electrical Applications) .....	23
Table 25 – HGT-EL Electrical Cabinet Door Ground Stud (Electrical Applications) .....	23
Table 26 – Torque for Hydraulic Valves Mounting Bolts.....	25
Table 27 – Torque for Orifices on Hydraulic Manifolds.....	25
Table 28 – Torque for Stauff or Hydac Hose/Pipe Clamps Mounting Bolts.....	26
Table 29 – Torque for Stopflex Hose Bands Mounting Bolts .....	26

Table 30 – Heavy-Duty Hose Clamp (T-Bolt Style) .....	27
Table 31 – Torques for Hydraulic Motors Mounting Bolts .....	27
Table 32 – Bosh Rexroth DBDS Pressure Relief Valves .....	27
Table 33 – Bladder Accumulator Neck Adaptor Specifications .....	28
Table 34 – Numatics 2012 & 2035 Air Valve Assemblies .....	29
Table 35 – Numatics ISO 1, 2 & 3 Air Valve Assemblies .....	30
Table 36 – Code 61 Split Flange Assemblies .....	32
Table 37 – Code 62 Split Flange Assemblies .....	32
Table 38 – CAM Follower Torque Specifications .....	33
Table 39 – EOAT Tube Retainer Pin Torque Specification .....	33
Table 40 – COOLPIK Vacuum/Blow Pin Torque Specifications .....	33
Table 41 – Mold/Hot Runner Lift Bars Mounting Screws Torque Specifications .....	35
Table 41 – Neck Ring Plugs Torque Specifications .....	35

## REVISION LOG

Rev.	Remarks
72	Updated torque requirements for EOAT Tube Retainer Pins in section 19.2. Section 17.8 Torque values for Hydac PTs reviewed with Hydac (Feb. 16, 2022) and increased from 20 N-m to 40 N-m. The purpose of the increased torque is to reduce/eliminate oil leakage from PT and fitting interface. Both Hydac and Husky test results show insignificant effect of increased torque on PT performance (i.e. insignificant null point shift).
71	Added section 19.13: Torque Specification for NexPET Core Sleeve Set Screws. DLO specifications updated (2205)
70	Updated CoolPik Vacuum/Blow Pin Torque Specifications Table 40 with values for M20 blow pins
69	Removed Adhesive info and moved to HS 897 – Adhesive Standard. Left Torque/Loctite info for clamp fasteners.
68	Section 17.08 Torque values added for new Hydac PT HPN 9247632
67	Lubrication notes added to section 14 - Torque values for fittings (HGT-FT)
66	Section 14 Torque values for fittings (HGT-FT) reviewed and updated: Section 14.1 relocated and revised to clarify assembly lubrication practices. Tables 12, 13, 14, 15, 18 and 19 updated as per the latest industry standards from Parker and Manuli. Section 17.11 added: Torque value for male pressure test point specified as per latest Hydac catalog.
65	<p>ORFS hose end fittings specifications: Increased torque values in table 13. Note: Previous torque values were too low especially for the smaller sizes and failed a pull test audit. Manuli torque values for nut tightening have been tested and approved. Warning: Husky torque specifications apply to lubricated parts while Manuli's apply in dry conditions. As a result, Husky exceeds Manuli's recommended preload.</p> <p>DLO Details 2015 specifications: Sheet 1: Added Spade terminal "S0" and "S8" Code. Sheet 6: HPN 7404990 updated AWG and Torque value. HPN 5832899 updated AWG value. Sheet 8: Added * Larger termination screws Sheet 10: HPN 2172625 added load side termination details Sheet 11: Added HPN 2351717 Sheet 12: Added HPN 6344019 Sheet 14: Added HPN 8425223</p>

64	DLO Details 1933 table updated to reflect current product usage along with torque value consolidation - See section 15 or DLO Details (English) 1937 or DLO Details (Chinese) 1937 specifications
63	DLO device torque specifications changes (DLO Details 1933) - See section 15 or <a href="#">HGT-EL DLO</a>
62	Unit changed from ft-lb to in-lb in Table 22 - HGT-EL Metric and Imperial Screws, Mounting Hardware (Electrical Applications) to align with other tables and tooling in use
61	HF and Cxx stopper code notes updated in <a href="#">HGT-EL DLO</a>
60	Section 17.6 Added value for 2.5" G2 Section 17.5 Updated table for DBDS relief valves
59	Added Section 17.10 for Numatics air valve assemblies
58	Section 17.8 updated. Old Hydac pressure transducer (HPN 3875996) replaced with new (HPN 7980938)
57	Added torques for Stopflex hose bands and heavy-duty hose clamp (T-Bolt style)
56	Added torque for electrical cabinet door ground stud
55	Updated as per SR 51455: Added note/picture for <u>Cold Half and Hot Runner Mounting to Machine Platen in Husky General Torque (HGT) - Standard Applications</u>
54	Updated as per SR 50799: Added sections 19.9, 19.10, 19.11, 19.12. Updated Sections 19.5, 19.6, 19.7, 19.9. Replaced and moved the table from section 19.7 to section 19.8
53	Added torque specifications for Premolded Cables, Electrical Applications). Bookmarks to multiple tables added. Table for HGT-35 specifications updated (Stainless steel A2, socket head cap screw application added)
52	Table for HGT-EL Heater Bands, Electrical Applications updated. Torque values for UNC # 1/4 - 20 spider straps and post terminal nut added. Torque values for Danfoss pressure transducers added (see section 17.9)
51	Added torque specifications for Neck Ring Plugs
50	Section 15 – HGT-EL Heater Bands, Electrical Applications updated. Torque value applied to ground stud nut specified.
49	Section 4 – References updated for HGT 80, 50 and 35 torque calculations (units of measure added)
48	Torque value for solid state relay added
47	2739013 CAM follower torque specifications updated
46	Table 1 updated and new Figure 1 added to clarify Husky General Torque Standard Applications (#1 to 8)
45	Torque values for Watlow heater bands added
44	Updated torque values for Watlow heater bands, torque values for Hydac oil level indicators added (see section 17.7), torque values for Hydac pressure transducers added (see section 17.8). HGT-EL DLO updated as per latest master
43	Updated torque values for HGT-LHCS (Low Head Cap Screws)
42	Section 19.1
41	Baumuller torque values in HGT-EL DLO updated to reflect mid-range torque values
40	Minor addition to sheet 6 in HGT-EL DLO as per manufacturing request
39	HGT-LHCS (Low Head Cap Screws) specifications added (section 13). Warning section added (section 5)
38	Section 13 updated (HGL-EL). Torque values for DLO related connections removed and consolidated into a separate document: HGT-EL DLO
37	Updated torque values for COOLPIK blow/vacuum pins in section 19.3 . Reference SIR 105554

<b>HUSKY</b>	<b>HS 252 - STANDARD ASSEMBLY TORQUES</b>		Page	6 of 49
	<b>Revision Level - 72 - PUBLISHED</b>	<b>Security Level - PUBLIC</b>	Standard No.	HS 252

36	Torque values for heater bands added/updated
35	Added note that states: "this document has a duplicate copy that's published to <a href="http://www.husky.co">www.husky.co</a> , all future revisions must be posted to <a href="http://www.husky.ca">www.husky.ca</a> "
34	Reference to Ampco 18 mounting screws removed
33	Added screw interchangeability notes in tables 4, 5, 6, and 8. Added screw interchangeability warning in section 5
32	Added new Section 17 for PET Mold and Hot Runner Special Torque Applications
31	Tables under section 15.8 reformatted (bladder accumulator neck adaptor specifications)
30	Torque values for accumulator neck adaptors added
29	Application notes (section 5.1) reviewed and updated: Torque values for high temperature applications (>150°C) statement clarified
28	HGT-EL torque values for Breakers, fuses and lugs updated
27	Baumuellr BM44XX Servo Drive Torque values added
26	Torque values for SAE plugs reviewed and updated
25	CAM follower torque values have been in Section 15.7
24	Torque values added to HGT-EL Lugged Connections - Electrical Applications
23	Torque values for SAE plugs updated
22	Torque values for Siemens 5SY series breaker added
21	Torque values for Woehner and Ferraz Shawmut fuse holder added
20	Torques for Bosch Rexroth DBDS pressure relief valves added (see section 17.5)
19	Lubricants section removed (transferred to HS 609)
18	Section 7.1, gearbox oil added
17	Hoist ring torquing requirements updated (SR 13841)
16	Remove note in revision 15
15	Add note for 4mm socket option for M10 (see section 10, B note)
14	Updated 'Table 1 – Husky General Torque Standards Applications': HR and Mold Liftbars with M30 installations to use HGT-35 – SR13141
13	Updated 'Table 1 – Husky General Torque Standards Applications': HR Liftbars to use HGT-50 as well – SR13141
12	Torques for electrical components added. References to "Husky Classes" added (e.g. Unbrako, Holokrome, YFS, etc. socket head cap screws).
11	Added applications notes for adhesives usage and selection (section 7.2.1 and 7.2.2 added)
10	Table 1 and application notes (section 5.1) updated to clarify the default preload (HGT-80, 50 or 35). Drawing specifications section updated (see section 14). Torque table shown on assembly drawings replaced by a note referring to the HS 252.
9	Approved hydraulic oils specified in HS 207. Reference to HS207 added to "Lubricants for General Application" section (Table 2). Note: table 2 transferred to HS 609 (see revision 19)
8	Added Manuli hose fittings, torque tolerances changed to +/-4% (section 6 updated)
7	Torque values applied to threaded rod applications and maximum allowable preload on 10.9 fasteners
6	New torque chart for AMPCO 18 applications added (see section 15.5), FFWR torque values for ORFS fittings added
5	Section 4 references added, section 6 torque tolerances added, tolerance values reviewed by tool supplier, document title changed.
4	New standard template used, torque values for SAE plugs updated, bulkhead locknut torque values added, torque for BSPT fittings and plugs added, lubricant section modified, torque tolerances added, etc.
3	Torque values for grade 10.9 and 12.9 screws consolidated, torque values for hydraulic applications and split flanges added, drawing specifications section updated, etc.
2	New format, new part numbers for FGL-2 grease, updated notes and units of measure
1	Published to Site
0	Original Issue

## 1 SCOPE

HGT (Husky General Torque) is a general torque standard that applies to threaded connections that do not have their respective torque values indicated on the drawing. Any other torque values such as the supplier's recommended torque specifications specified in Section 17 or any other deviations from the general standard must be individually specified on the drawing. Any deviations from this standard must be justified by calculations.

## 2 PURPOSE

To provide a list of general torque values and lubrication practices to be used on Husky product.

## 3 DOCUMENT CONTROL

Revisions to this document shall be authorized by Corporate Operations.

## 4 REFERENCES

The torque values specified in this document come from the following Industry Standards, Suppliers Catalogs and/or formulae:

HGT-80 Metric Fasteners	T = K.F.d - Torque T in Newton-meter - Coefficient of friction $\mu = 0.12$ - Torque coefficient K ( $0.15 \leq K \leq 0.17$ ) - Induced screw load F in Newton - Nominal diameter d in meter - ISO 898-1 (grades 12.9 & 10.9) and ASTM A574	Standard proofload ratios: 80, 50 and 35%. E.g. 80% preload means that the torque will produce enough energy to achieve 80% of what the bolt is capable of without permanent deformation.
HGT-80 Imperial Fasteners		
HGT-50 Metric Fasteners		
HGT-50 Imperial Fasteners		
HGT-35 Metric Fasteners		
HGT-35 Imperial Fasteners		
HGT-SS Metric Set Screws	ISO 898/5-1980 Table 5 and ASTM F912-1986 Table 2	
HGT-SS Imperial Screws	ASTM F912-1986	
HGT-LHCS Metric Screws	Torque values provided by manufacturer	
HGT-FT ORFS Tube Ends	Parker Catalog 4300 (April 2017)	
HGT-FT SAE and BSPP Ends	Parker Catalog 4300 (April 2017)	
HGT-FT ORFS Hose Ends	Manuli Hydraulics catalog 2020	
HGT-FT JIC Ends	Parker Catalog 4300 (April 2017)	
HGT-FT NPT and BSPT Plugs and Fittings	Parker Catalog 4300 (April 2017)	
HGT-FT Flareless Tube Ends	Parker Catalog 4300 (April 2017)	
HGT-FT SAE Plugs	Parker Catalog 4300 (April 2017)	
HGT-FT Bulkhead Locknuts	Parker Catalog 4300 (April 2017)	
HGT-FT BSPP Plugs	Former Luxembourg Machine torque standard (LTML111)	
HGT-FT Metric Plugs	Former Luxembourg Machine torque standard (LTML111)	
HGT-EL Metric and Imperial Screws	Electric Components Supplier	
Torque for Hydraulic Valves Mounting Bolts	Torque values provided by manufacturer	
Torque for Orifices on Hydraulic Manifolds	Former Luxembourg Machine torque standard (LTML111)	
Torque for Hose/Pipe Clamps Mounting Bolts	Former Luxembourg Machine torque standard (LTML111)	
Torques for Hydraulic Motors Mounting Bolts	Torque values provided by manufacturer	
Code 61 Split Flange Assemblies	ISO 6162-1994	
AMPCO 18 Applications	Torque values provided by manufacturer	
Code 62 Split Flange Assemblies	ISO 6162-1994	



## 5 WARNINGS

Always use the correct parts and the proper torques. Incorrect fastener connections can dangerously weaken assemblies. Ensure that all safety information, instructions and warnings such as shown in the two examples below are read and understood before any operation or any maintenance procedures are performed.

### CAUTION!

Mechanical hazard – risk of equipment damage. Use of improper torque can result in equipment damage. Consult the assembly drawings for the torque specifications before referring to the torque charts in this section.

### WARNING!

Molten plastic spray hazard - risk of serious injury and equipment damage. If incorrectly sized screws are used, equipment damage may occur that could result in uncontained molten plastic spray. If replacing the screws, only use the screw sizes specified in the machine bill of material.


## 6 APPLICATIONS

HGT consists of seven torque standards HGT-80, HGT-50, HGT-35, HGT-SS, HGT-LHCS, HGT-FT and HGT-EL as shown in Table 1. For mechanical applications, screws are torqued to the HGT-80, HGT-50, HGT-35 or HGT-LHCS standards. For electrical applications, screws and other components are torqued to the HGT-EL standard. Set screws are torqued to the HGT-SS standard and fittings to the HGT-FT standard. Deviations from Husky General Torque Standards for Special PET Mold and Hot Runner applications are listed below and are cited in detail in section 19.

- 19.1 CAM Follower Torque Specifications
- 19.2 EOAT Tube Retainer Pin Torque Specification
- 19.3 CoolPik Vacuum/Blow Pin Torque Specifications
- 19.4 CoolPik Moving Puck Installation Torque Specification
- 19.5 CoolPik Plate Mounting Torque Specification
- 19.6 Mold/Hot Runner Lift Bars Mounting Screws Torque Applications
- 19.7 Gib/Wear Plate Mounting Screws Torque Specification
- 19.8 Neck ring plugs Torque Specification
- 19.9 Stack Inserts Torque Specification
- 19.10 Torque Specification for Water Manifolds to Slides
- 19.11 Torque Specification for Slide to Connecting Bars
- 19.12 Torque Specification for EOAT Assy. to Robot
- 19.13 Torque Specification for NexPET Core Sleeve Set Screws



**Figure 1 – Husky General Torque (HGT) - Standard Applications (# 1 to 8)**



**Table 1 – Husky General Torque (HGT) - Standard Applications**

Application		Hardware		Base/Threaded Material	Torque Standard
Mechanical	<b>Hot Runner Assemblies</b> <div>1</div>	Screws and Threaded Rods	- DIN 912-12.9 SHCS* - DURLOK-12.9-UNB HHS - DIN 976-12.9 ROD	Steel Cast Iron	HGT-80
		Set Screws	- ISO 898/5-45H - ASTM F912	N/A	HGT-SS
		Low Head Cap Screws	- DIN 7984	N/A	HGT-LHCS
	<b>Cold Half Assemblies (including Cavity plate assembly)</b> <div>2</div>	Screws and Threaded Rods	- DIN 912-12.9 SHCS* - DURLOK-12.9-UNB HHS - DIN 933 & 931-10.9 HHCS - DIN 976-12.9&10.9 ROD	Steel Cast Iron	HGT-50
		Set Screws	- ISO 898/5-45H - ASTM F912	N/A	HGT-SS
		Low Head Cap Screws	- DIN 7984-10.9 LHCS	N/A	HGT-LHCS
	<b>Cold Half and Hot Runner Mounting to Machine Platen</b> <div>3</div>	SHCS	- DIN 912-12.9 SHCS*	Cast Iron	HGT-50**

\* Referred to as “Husky Classes 1, 2, 3 & 4” in HS 258


\*\* When using hex tool adapter to access mold mounting screws, no de-rating of torque value is required - See Figure 2

/... Continuing on next page

Application		Hardware		Base/Threaded Material	Torque Standard
Mechanical	Machine Assemblies 4	Screws and Threaded Rods	- DIN 912-12.9 SHCS* - DURLOK-12.9-UNB HHS - DIN 933 & 931-10.9 HHCS - DIN 976-12.9&10.9 ROD - ASTM A574 SHCS	Steel Cast Iron	HGT-50
		Set Screws	- ISO 898/5-45H - ASTM F912	N/A	HGT-SS
	All Assemblies Using a Weaker Base Material 5	Screws and Threaded Rods	- DIN 912-12.9 SHCS* - DURLOK-12.9-UNB HHS - DIN 933 & 931-10.9 HHCS - DIN 976-12.9&10.9 ROD - DIN 7991-10.9 FHCS - ISO 7380-10.9 BHCS - ASTM A574 SHCS	Cast Aluminum, Aluminum Plate	HGT-35
6	Hydraulic, Lubrication, Air and Water	Hose and Tube Fittings	- O-ring face Seal - JIC (37° Flared) - NPT, BSPP, Bite - SAE Straight Thread	N/A	HGT-FT
7	Electrical	Screws and other components	- Steel, Al& Cu, Brass screws	N/A	HGT-EL
8	Hoist Rings	Screws	- As supplied with Hoist Ring	N/A	Follow Supplier recommendation

\* Referred to as “Husky Classes 1, 2, 3 & 4” in HS 258

**Figure 2 – Using Hex Tool Adapter to Access Mold Mounting Screws**



## 6.1 APPLICATION NOTES

- Washers are recommended for oversized holes and slots.
- Heavy washers (DIN 7349) are recommended for cast aluminum applications.
- The HGT-80 standard is recommended for the majority of Hot Runner products: These high strength and/or high fatigue applications use grade 12.9 bolts that will not crush, gall, warp or fracture the joint material under preload (e.g. high-strength alloy steel).
- The HGT-50 standard is recommended for the majority of Machine and Mold product applications. HGT-50 ensures that the area below the screw head does not bear into the seating material and the threads do no shear upon torquing.
- The HGT-35 standard is recommended for those applications where the yield strength of the base material would otherwise be exceeded under a 50% preload. An example is clamping a cantilevered section such as a belt clamp that is subject to bending stress.
- Torque values for high temperature applications (>150°C) should be calculated and individually specified on the drawing as required. If no values are indicated on the drawing, the general HGT standard should be used (e.g. HGT-50 for Machine and Mold applications, HGT-80 for Hot Runner applications).
- In all applications the joint must be designed to carry the load safely and without separation.
- Screw sizes and torque values must be supported by calculations for externally applied loads that are subjected to fatigue action such as pressurized vessels.
- When maintenance or service requires the replacement of screws, it is recommended that they be the same ones specified in the machine Bill of Material. Due to the interchangeability between some metric and imperial screws, incorrect sizes may provide insufficient bolt preload over time.

## 7 TORQUE TOLERANCES

The more accurate the method of controlling tightness the more of the strength of the fastener can be utilized. The tolerance values specified in this standard pertain to the tool's accuracy and not the induced fastener's load that is affected by other variables such as lubrication, clamped materials, temperature, etc. For example, assembly torque wrenches should be calibrated to stay within +/-4% when applying HGT-50, 80 or 35 and the fastener's induced load accuracy can be expected to range from +/- 10-20%.

## 8 LINK TO HS DOCUMENTS

HS 207 - Approved Hydraulic Fluids: Use products shown in table 1.

HS 609 - Lubricants and coolants: Use products shown in tables 1, 2 or 3 based on applications.

HS 897 - Adhesives: Use products shown in table 2 for soft joint applications.

## 9 HGT-80 STANDARD (SCREWS AND THREADED RODS - 80% PRELOAD)

The following torques must be applied to screws in order to produce the desired 80% preload.

**Table 2 – HGT-80 Metric Fasteners**

Grade 12.9 Fasteners			
Socket Head Cap Screw* (DIN912)			
Durlock Hex Head Cap Screw (UNB 12.9)			
Threaded Rod (DIN976)			
Size	Torque (+/- 4%)		Induced Screw Load (N)
	N-m	ft-lb	
M4	4.6	3.4	6800
M5	9.5	7.1	11000
M6	16	12	15600
M8	39	29	28400
M10	77	57	45000
M12	135	100	65000
M14	215	160	90000
M16	330	245	122000
M20	650	480	190000
M24	1100	810	273000
M30	2250	1660	435000
M36	3850	2840	634000
M42	6270	4630	870000
M48	8560	6320	1140000

**Table 3 – HGT-80 Imperial Fasteners**

ASTM A574 Fasteners			
Imperial Socket Head Cap Screw			
Size	Torque (+/- 4%)		Induced Screw Load (N)
	N-m	ft-lb	
#8	5	4	7000
#10	7	5	8700
1/4	16	12	15800
5/16	35	25	26100
3/8**	60	45	38000
7/16**	95	70	53000
1/2	150	110	71000
5/8	290	210	108000
3/4**	500	360	160000
7/8	790	580	222000
1	1180	865	291000
1 1/8	1680	1240	367000
1 1/4	2400	1750	466000
1 3/8	3100	2300	555000
1 1/2	4100	3040	676000
1 3/4	6500	4800	911000

\* Referred to as “Husky Classes 1, 2, 3, and 4” in HS 258.

\*\* When maintenance or service requires the replacement of screws, it is recommended that they be the same ones specified in the machine Bill of Material. Due to the interchangeability between some metric and imperial screws, incorrect sizes may provide insufficient bolt preload over time.

## 10 HGT-50 STANDARD (SCREWS AND THREADED RODS - 50% PRELOAD)

The following torques must be applied to screws in order to produce the desired 50% preload.

**Table 4 – HGT-50 Metric Fasteners**

Grade 12.9 and 10.9 Fasteners			
Socket Head Cap Screw* (DIN912)			
Hex Head Cap Screw (UNB 12.9, DIN933, DIN931)			
Threaded Rod (DIN976)			
Size	Torque (+/- 4%)		Induced Screw Load (N)
	N-m	ft-lb	
M4	3	2.2	4250
M5	6.2	4.6	8900
M6	10	7	9800
M8	25	18	17800
M10	53	40	31500
M12	95	70	47000
M14	130	95	56000
M16	220	160	85000
M18**	270	200	93000
M20	390	290	124000
M24	660	490	171000
M30	1300	960	272000
M36	2300	1700	396000
M42	3700	2700	544000
M48	5500	4000	714000

**Table 5 – HGT-50 Imperial Fasteners**

ASTM A574 Fasteners			
Imperial Socket Head Cap Screw			
Size	Torque (+/- 4%)		Induced Screw Load (N)
	N-m	ft-lb	
#8	3	2	4360
#10	4	3	5450
1/4	11	8	9900
5/16	22	16	16300
3/8**	40	30	24000
7/16**	60	45	33000
1/2	95	70	44000
5/8	180	135	68000
3/4**	310	230	100000
7/8	490	360	139000
1	750	550	182000
1 1/8	1040	770	230000
1 1/4	1480	1090	291000
1 3/8	1940	1430	347000
1 1/2	2580	1900	423000
1 3/4	4050	2990	570000

\* Referred to as “Husky Classes 1, 2, 3, and 4” in HS 258.

\*\* When maintenance or service requires the replacement of screws, it is recommended that they be the same ones specified in the machine Bill of Material. Due to the interchangeability between some metric and imperial screws, incorrect sizes may provide insufficient bolt preload over time.

## 11 HGT-35 STANDARD (SCREWS - 35% PRELOAD)

The following torques must be applied to screws in order to produce the desired 35% preload.

**Table 6 – HGT-35 Metric Fasteners**

Grade 12.9, 10.9 and A2 Fasteners			
Socket Head Cap Screw* (DIN912)			
Socket Head Cap Screw*** (Stainless Steel, A2)			
Hex Head Cap Screw (UNB 12.9, DIN933, DIN931)			
Flat Head Cap Screw (DIN7991)			
Button Head Cap Screw (ISO7380)			
Size	Torque (+/- 4%)		Induced Screw Load (N)
	N-m	ft-lb	
M4	2.1	1.5	2980
M5	4	3	4800
M6	9	7	7800
M8	19	14	14200
M10	37	27	22000
M12	50	37	24500
M16	125	90	49000
M20	250	185	79000
M24	440	325	115000
M30	875	650	182000
M36	1530	1130	265000

**Table 7 – HGT-35 Imperial Fasteners**

ASTM A574 Fasteners			
Imperial Socket Head Cap Screw			
Size	Torque (+/- 4%)		Induced Screw Load (N)
	N-m	ft-lb	
#8	1	1	2670
#10	3	2	3100
1/4	7	5	5800
5/16	14	10	9800
3/8**	23	17	14200
7/16**	38	28	20000
1/2	58	42	26700
5/8	110	81	41000
3/4**	180	135	60000
7/8	300	220	83000
1	450	330	111000
1 1/8	620	460	138000
1 1/4	890	660	175000
1 3/8	1170	860	208000
1 1/2	1550	1140	254000
1 3/4	2450	1790	342000

\* Referred to as “Husky Classes 1, 2, 3, and 4” in HS 258.

\*\* When maintenance or service requires the replacement of screws, it is recommended that they be the same ones specified in the machine Bill of Material. Due to the interchangeability between some metric and imperial screws, incorrect sizes may provide insufficient bolt preload over time.

\*\*\* HGT-35 is the proper torque for stainless steel screws (strength of stainless steel screw is 70% of grade 10.9).

## 12 HGT-SS STANDARD (SET SCREWS)

The following torques must be applied to set screws.

**Table 8 – HGT-SS Metric Set Screws**

ISO 898/5-45H Set Screws Metric Socket Set Screw (DIN913-14-15-16)		
Size	Torque (+/- 4%)	
	N-m	ft-lb
M3	0.9	0.66
M4	2.2	1.6
M5	4	3
M6	7.2	5.3
M8	17	12.6
M10	33	24
M12	54	40
M16	134	99
M20	237	175
M24	440	325

**Table 9 – HGT-SS Imperial Screws**

ASTM F912 Set Screws Imperial Socket Set Screw ANSI B18.3.1)		
Size	Torque (+/- 4%)	
	N-m	ft-lb
#5	1.1	0.8
#6	1.1	0.8
#8	2.7	2
#10	4	3
1/4	9.5	7
5/16	19	14
3/8	33	24
1/2	70	52
9/16	70	52
5/8	150	110
3/4	270	200
7/8	410	300
1	570	420



## 13 HGT-LHCS STANDARD (LOW HEAD CAP SCREWS)

The following torques must be applied to low head cap screws.

**Table 10 – HGT-LHCS Metric Low Head Cap Screws**

Grade 10.9 Low Head Cap Screws Low Head Cap Screws (DIN 7984)		
Size	Torque (+/- 4%)	
	N-m	in-lb
M4	2.7	24
M5	5.4	48
M6	9.15	81
M8	22	195
M10	44	389
M12	77	682
M16	190	1681
M20	371	3284

## 14 HGT-FT STANDARD (FITTINGS)

The following tables provide the recommended torque values required for the safe and effective operation of the fittings using a torque wrench or other methods such as “Turn From Finger Tight”, “Flats From Finger Tight” or “Flats from Wrench Resistance”. For TFFT or FFFT, the joint should be hand tightened snugly and then tightened with a wrench by the number of flats or turns indicated by the table. For “FFWR”, the joint should be tightened snugly with a wrench and then tightened again with the same wrench by the number of flats indicated by the table. The torque method of assembly is the preferred method of assembly. It reduces the risk of human error during assembly that is more prevalent in the “FFWR” method. To ensure the most accurate assembly of the fitting, it is strongly recommended that the torque method be utilized.

### 14.1 IMPORTANT NOTES

- O-rings must always be lubricated.
- Refer to the notes in red and the following symbols to determine if lubricant should be applied to threads.




Apply lubricant to threads



Do not apply lubricant to threads

- Values are for steel fittings in steel ports.
- For stainless steel fittings, please use the upper limit of torque range. Exclusion: NPT and BSPT fittings.
- For brass, aluminum (and other soft metals), decrease torque value by 35%. Exclusion: NPT and BSPT fittings.
- For NPT and BSPT elbows, never back off to achieve alignment.
- For ferrule (bite) fittings, manually screw the nut on the fitting body until finger tight. Continue to tighten the joint with a wrench by the number of flats indicated in the table. If the fitting body was used for ferrule pre-set, the nut must be re-tightened to the same fitting body used earlier in pre-set.
- Assembled parts (nut and adapter) must have identical plating.
- Torque values shown apply to the ends indicated by arrows.


**Table 11 – HGT-FT ORFS Tube Ends**

O-ring Face Seal Tube Ends				
				
SAE Dash Size	Thread Size Inch	Tube Side Torque * (+10% - 0) Nm (ft-lb)	FFWR Tube Nuts (min-max)	FFWR Swivel & Hose Ends (min-max)
-4	9/16 - 18	25 (18)	1/4 - 1/2	1/2 - 3/4
-6	11/16 - 16	40 (30)	1/4 - 1/2	1/2 - 3/4
-8	13/16 - 16	55 (40)	1/4 - 1/2	1/2 - 3/4
-10	1 - 14	80 (60)	1/4 - 1/2	1/2 - 3/4
-12	1-3/16 - 12	115 (85)	1/4 - 1/2	1/3 - 1/2
-16	1-7/16 - 12	150 (110)	1/4 - 1/2	1/3 - 1/2
-20	1-11/16 - 12	205 (150)	1/4 - 1/2	1/3 - 1/2
-24	2 - 12	315 (230)	1/4 - 1/2	1/3 - 1/2
-32	2 1/2 - 12	510 (375)	1/4 - 1/2	1/3 - 1/2

**\* IMPORTANT:** Recommended torques values are only applicable for nut tightening in dry conditions (no oil or lubrication on threads and sealing surfaces, only O-rings must be lubricated). For brass, aluminum (and other soft metals), decrease torque value by 35%. However, FFWR is the same.






**Table 12 – HGT-FT ORFS Hose Ends (Manuli Hose Fittings)**

O-ring Face Seal						
						
SAE Dash Size	Hose ID	Thread Size	Recommended Torque *		Rotation Angle (degrees)	FFFT Hose Ends
			Nm (0, +10%)	ft-lbs (0, +10%)		
-4	1/4"	9/16"-18	26	19	45°	3/4
-6	3/8"	11/16"-16	42	31	45°	3/4
-8	1/2"	13/16"-16	57	42	60°	3/4
-10	5/8"	1"-14	85	63	45°	1
-12	3/4"	1 3/16"-12	122	90	45°	3/4
-16	1"	1 7/16"-12	156	115	45°	3/4
-20	1 1/4"	1 11/16"-12	200	148	45°	3/4
-24	1 1/2"	2"-12	256	189	45°	3/4

**\* IMPORTANT:** Recommended torques values are only applicable for nut tightening in dry conditions (no oil or lubrication on threads and sealing surfaces, only O-rings must be lubricated).




**Table 13 – HGT-FT SAE and BSPP Ends**

Adjustable and Non-Adjustable SAE and BSPP Ends (Plugs excluded)				
SAE Dash Size	Thread Size Inch	Torque * (+10% - 0)		
		JIC, Ferrule Fittings	JIC, Ferrule & Pipe Fittings	Face Seal Fittings
		Adjustable 	Non-Adjustable 	Adjustable and Non-Adjustable 
		Nm (ft-lb)	Nm (ft-lb)	Nm (ft-lb)
-4	7/16 - 20	20 (15)	29 (15)	20 (15)
-6	9/16 - 18	40 (30)	40 (30)	46 (35)
-8	3/4 - 16	70 (52)	70 (52)	80 (60)
-10	7/8 - 14	115 (85)	115 (85)	135 (100)
-12	1-1/16 - 12	185 (135)	185 (135)	185 (135)
-14	1-3/16 - 12	235 (175)	235 (175)	235 (175)
-16	1-5/16 - 12	270 (200)	270 (200)	270 (200)
-20	1-5/8 - 12	340 (250)	340 (250)	340 (250)
-24	1-7/8 - 12	415 (305)	415 (305)	415 (305)
-32	2-1/2 - 12	510 (375)	510 (375)	510 (375)

**\* IMPORTANT: Lubricate threads before assembly. Values in chart are for plated steel fittings in steel ports. For stainless steel fittings, use the upper limit of torque range. For brass and aluminum, decrease torque value by 35%.**





**Table 14 – HGT-FT JIC Ends**

JIC (37 Deg Flared Tube) Ends				
				
SAE Dash Size	Thread Size Inch	Assembly Torque * (+10% - 0) Nm (ft-lb)	Tube End FFWR	Hose End or Swivel Nut FFWR
4	7/16 - 20	18 (13)	2 1/2	2
6	9/16 - 18	30 (22)	2	1 1/2
8	3/4 - 16	57 (42)	2	1 1/2
10	7/8 - 14	81 (60)	1 1/2	1 1/2
12	1-1/16 - 12	115 (84)	1 1/2	1 1/4
14	1-3/16 - 12	135 (100)	1 1/2	1 1/4
16	1-5/16 - 12	160 (118)	1 1/2	1
20	1-5/8 - 12	230 (168)	1	1
24	1-7/8 - 12	265 (195)	1	1
32	2-1/2 - 12	360 (265)	1	1
40	3-12	Not Applicable	1	1

**\* IMPORTANT: Torque values are for unlubricated carbon steel components and properly lubricated stainless-steel components.**





**Table 15 – HGT-FT NPT and BSPT Plugs and Fittings**

NPT and BSPT Fittings and Plugs		
Torque *		
		
NPTF Inch	BSPT Inch	TFFT (min-max)
1/8-27	1/8-28	2 - 3
1/4-18	1/4-19	2 - 3
3/8-18	3/8-19	2 - 3
1/2-14	1/2-14	2 - 3
3/4-14	3/4-14	2 - 3
1 - 11-1/2	1 - 11	1.5 - 2.5
1-1/4 - 11-1/2	1-1/4 - 11	1.5 - 2.5
1-1/2 - 11-1/2	1-1/2 - 11	1.5 - 2.5
2 - 11-1/2	2 - 11	1.5 - 2.5

**\* IMPORTANT:**  
Carbon & stainless steel components: Apply lubricant to male pipe threads if not pre-applied. The first to two threads should be left uncovered to avoid system contamination.



**Table 16 – HGT-FT Flareless Tube Ends**



Ferrule (Bite) Fittings		
Torque *		
		
SAE Dash Size	Thread Size Inch	Nut TFFT (min-max)
4	7/16 - 20	1/6 - 1/4
6	9/16 - 18	1/6 - 1/4
8	3/4 - 16	1/6 - 1/4
10	7/8 - 14	1/6 - 1/4
12	1-1/16 - 12	1/6 - 1/4
14	1-3/16 - 12	1/6 - 1/4
16	1-5/16 - 12	1/6 - 1/4
20	1-5/8 - 12	1/6 - 1/4
24	1-7/8 - 12	1/6 - 1/4
32	2-1/2 - 12	1/6 - 1/4

**\* IMPORTANT:**  
Carbon steel components: Lubricate threads before assembly. No additional lubrication is required for stainless steel fittings as the nuts are pre-lubricated.



**Note:** For final assembly of swivel nut fittings (R6BU, C6BU and S6BU), a 3/4 TFFT is required for all sizes.



**Table 17 – HGT-FT SAE Plugs**

SAE Straight Thread Plugs			
SAE Dash Size	Thread Size	Torque * (+10% - 0)	
		Hollow Hex Plug 	Hex Plug 
	Inch	Nm (ft-lb)	Nm (ft-lb)
-2	5/16 - 24	7 (5.2)	10 (7.4)
-3	3/8 - 24	11 (8.1)	18 (13)
-4	7/16 - 20	20 (14.8)	29 (21)
-5	1/2 - 20	28 (20.7)	32 (23)
-6	9/16 - 18	40 (30)	40 (30)
-8	3/4 - 16	70 (52)	70 (52)
-10	7/8 - 14	115 (85)	115 (85)
-12	1-1/16 - 12	185 (135)	185 (135)
-14	1-3/16 - 12	235 (175)	235 (175)
-16	1-5/16 - 12	270 (200)	270 (200)
-20	1-5/8 - 12	340 (250)	340 (250)
-24	1-7/8 - 12	415 (305)	415 (305)
-32	2-1/2 - 12	510 (375)	510 (375)

**\* IMPORTANT:**  
Lubricate threads before assembly.




**Table 18 – HGT-FT Bulkhead Locknuts**

Bulkhead Locknuts		
SAE Dash Size	Torque * (+10% - 0)	
	O-ring Face Seal Ends 	JIC or ferrule Ends 
	Nm (ft-lb)	Nm (ft-lb)
4	20 (15)	18 (13)
6	34 (25)	35 (25)
8	75 (55)	65 (50)
10	115 (75)	115 (85)
12	180 (125)	180 (135)
14	230 (170)	230 (170)
16	270 (200)	270 (200)
20	330 (245)	330 (245)
24	365 (270)	365 (270)
32	Not Applicable	420 (310)

**\* IMPORTANT:**  
Torque values are only applicable for nut tightening in dry conditions




**Table 19 – HGT-FT BSPP Plugs**

BSPP Plugs	
Thread Size	Torque * (+10% - 0) ↓ 
Inch	Nm (ft-lb)
1/8 - 28	13 (9.6)
1/4 - 19	30 (22)
3/8 - 19	60 (44)
1/2 - 14	80 (60)
3/4 - 14	140 (105)
1 - 11	200 (155)
1-1/4 - 11	400 (295)
1-1/2 - 11	450 (330)

**\* IMPORTANT:  
Lubricate threads  
before assembly**



**Table 20 – HGT-FT Metric Plugs**

Metric Plugs	
Thread Size	Torque * (+10% - 0) ↓ 
Metric	Nm (ft-lb)
M42	400 (295)
M48	500 (370)
M52	600 (440)
M60	800 (590)
M64	850 (630)
M68	1000 (740)
M70	1100 (810)
M75	1300 (960)
M80	1550 (1150)
M85	1800 (1330)
M90	2000 (1480)

**\* IMPORTANT:  
Lubricate threads  
before assembly**



## 15 HGT-EL STANDARD (ELECTRICAL APPLICATIONS)

The following torque values should be used in the case of electrical applications. Notes: For non-standard components, use the recommended manufacturer's specifications. For DLO (Diesel Locomotive Cable) related connections, please call Husky Service or refer to section [20.1](#) - DLO Device Details.

**Table 21 – HGT-EL Metric and Imperial Screws, Mounting Hardware (Electrical Applications)**

Metric and Imperial Screws				
Size		Torque Nm (in-lb) (+10% - 0)		
		Steel	Al & Cu	Brass
<b>M3</b>	<b>#4</b>	0.7 (6.2)	0.3 (2.6)	0.6 (5.3)
<b>M3.5</b>	<b>#6</b>	1 (8.8)	0.5 (4.4)	0.8 (7.1)
<b>M4</b>	<b>#8</b>	1.3 (11.5)	0.7 (6.2)	1.2 (10.6)
<b>M5</b>	<b>#10</b>	1.9 (16.8)	1 (8.8)	1.7 (15.0)
<b>M6</b>	<b>1/4</b>	6 (53.1)	3 (26.5)	5 (44.2)
<b>M8</b>	<b>5/16</b>	8 (70.8)	4 (35.4)	5 (44.2)
<b>M10</b>	<b>3/8</b>	10 (88.5)	5 (44.2)	8 (70.8)

**Table 22 – HGT-EL Heater Bands (Electrical Applications)**

Heater Band Fasteners				
Fastener Size (Inch)	Fastener Type			
	Nickel Plated Dry	Nickel Plated Anti-Seize	Black Oxide Dry	Black Oxide Anti-Seize
UNC # 6 - 32	30 lb-in / 3.4 N-m	20 lb-in / 2.3 N-m	20 lb-in / 2.3 N-m	15 lb-in / 1.7 N-m
UNC # 8 - 32	40 lb-in / 4.5 N-m	30 lb-in / 3.4 N-m	25 lb-in / 2.8 N-m	20 lb-in / 2.3 N-m
UNC # 10 - 24	55 lb-in / 6.2 N-m	35 lb-in / 4.0 N-m	35 lb-in / 4.0 N-m	30 lb-in / 3.4 N-m
UNC # 1/4 - 20	80 lb-in / 9.0 N-m	55 lb-in / 6.2 N-m	50 lb-in / 5.6 N-m	45 lb-in / 5.1 N-m
UNC # 1/4 - 20 Barrel Bar Clamp* and Spider Straps	80 lb-in / 9.0 N-m	80 lb-in / 9.0 N-m	80 lb-in / 9.0 N-m	80 lb-in / 9.0 N-m
UNC # 5/16 - 18	80 lb-in / 9.0 N-m	80 lb-in / 9.0 N-m	80 lb-in / 9.0 N-m	80 lb-in / 9.0 N-m

Heater Band Ground Stud **	18 lb-in / 2.0 N-m maximum
Post Terminal Nut **	24 lb-in / 2.7 N-m maximum


\* For screws attached to each other through a 'common' barrel bar clamp

\*\* Use an open ended wrench to hold the nut closest to the heater as the wiring nut is torqued (threaded ground stud must not rotate).





**Figure 4 – Husky General Torque Chart**

<p>FOR TORQUE SPECIFICATIONS, REFER TO HS 252</p>	<p>METRIC </p> <p>THIS DRAWING AND INFORMATION CONTAINED WITHIN IS CONFIDENTIAL AND/OR PROPRIETARY TO HUSKY INJECTION MOLDING SYSTEMS LTD. OR ONE OF ITS SUBSIDIARIES ("HUSKY") AND MAY NOT BE COPIED, DISCLOSED OR USED, IN WHOLE OR IN PART, WITHOUT THE PRIOR WRITTEN CONSENT OF HUSKY.</p>
<p>WEIGHT</p> <p>- kg</p>	<p>NO INTELLECTUAL PROPERTY RIGHTS ARE GRANTED INCLUDING ANY LICENSE IMPLIED OR OTHERWISE.</p> <p>ALL RIGHTS RESERVED. COPYRIGHT 2004 HUSKY.</p>

## 17 SUPPLIER RECOMMENDED TORQUE SPECIFICATIONS

The following torque values are recommended by suppliers and must be followed unless otherwise specified on the drawing.

### 17.1 HYDRAULIC MANIFOLDS – TORQUE VALUES FOR SCREWS

**Table 26 – Torque for Hydraulic Valves Mounting Bolts**

Torque N-m (ft-lb) Min.-Max.										
Bolt Size	Bosh			Rexroth			Moog/Hydrolux			Hyd. Option Segment Manifold
	Prop. Valves	Direct Valves	Cartridges	Prop. Valves	Direct Valves	Cartridges	Prop. Valves	Direct Valves	Cartridges	
M5	6-8 (4.4-5.9)	6-8 (4.4-5.9)		6.2-8.9 (4.6-6.6)	6.2-8.9 (4.6-6.6)		5.8-7.8 (4.2-5.7)	7.2-8 (5.3-5.9)		8.9-9.8 (6.6-7.2)
M6	11-14 (8.1-10.3)	11-14 (8.1-10.3)		11-15.5 (8.1-11.4)	11-15.5 (8.1-11.4)		9.4-12.6 (6.9-9.3)	11.7-13 (8.6-9.6)		15.5-17 (11.5-12.6)
M8			26-31 (19-23)			23-32 (17-23)			27-30 (20-22)	32-35 (23-26)
M10	40-50 (30-37)	50-60 (37-44)		53-75 (39-55)	53-75 (39-55)		46-62 (34-45)	50-55 (37-40)		75-83 (55-61)
M12	90-120 (66-88)	85-100 (63-73)	90-105 (66-77)	91-130 (67-96)	91-130 (67-96)	77-110 (57-81)	80-108 (59-80)	90-100 (66-74)	90-100 (66-74)	110-121 (81-89)
M16			240-260 (178-192)			189-270 (139-199)			270-300 (199-221)	270-297 (200-219)
M20	450-560 (332-410)		450-500 (332-369)	301-430 (222-317)	301-430 (222-317)	364-520 (268-383)	391-529 (288-390)	495-550 (365-406)	495-550 (365-405)	520-572 (385-422)
M24						630-900 (464-664)			810-900 (598-664)	900-990 (665-730)
M30						1260-1800 (929-1327)			1620-1800 (1195-1328)	1800-1980 (1330-1460)
Lubricant	Hydraulic Oil									Grease

Note: Those values are mandatory, regardless of screw quality used.

### 17.2 HYDRAULIC MANIFOLDS – TORQUE VALUES FOR ORIFICES

**Table 27 – Torque for Orifices on Hydraulic Manifolds**


Hydraulic Manifolds – Orifices		
Bolt Size	Torque (+/- 4%)	
	N-m	ft-lb
M5	4	3
M6	6	4.5
M8	13.5	10
M10	27	20
Lubricant	Grease	

## 17.3 HOSE/PIPE CLAMPS – TORQUE VALUES FOR SCREWS


**Table 28 – Torque for Stauff or Hydac Hose/Pipe Clamps Mounting Bolts**

Clamp Type	Lubricant	Bolt Size	Clamp Size	Torque in Nm (ft-lb) (+/- 4%) with Clamping Material		
				Aluminum (AL)	Polypropylene (PP)	Polyamid (PA)
Single clamp Light series	Loctite	M6	0 to 6	12 (9)	8 (5.9)	10 (7.4)
Single clamp Heavy series		M10	1	30 (22)	12 (9)	20 (15)
			2	30 (22)	12 (9)	20 (15)
			3	35 (26)	15 (11)	25 (18)
		M12	4	55 (40)	30 (22)	40 (30)
		M16	5	120 (90)	45 (33)	55 (40)
		M20	6	220 (160)	80 (60)	150 (110)
		M24	7	250 (180)	110 (80)	250 (180)
Twin clamp		M6	1	N/A	5 (3.7)	6 (4.4)
		M8	2	N/A	12 (8.9)	12 (8.9)
			3	N/A		
			4	N/A		
	5		N/A	8 (5.9)	8 (5.9)	

**Table 29 – Torque for Stopflex Hose Bands Mounting Bolts**

Stopflex Hose Bands				
				
Hose Band	Hose Outside Diameter (mm)		Bolt Size (metric)	Bolt Tightening Torque
Model Number	Ø MIN	Ø MAX	Ø M	Nm (ft-lb) (+/- 4%)
STOPFA13135	13	13.5	M6	3 (2)
STOPFA1415	14	15	M6	3 (2)
STOPFA1718	17	18	M6	3 (2)
STOPFA1819	18	19	M6	3 (2)
STOPFA2122	21	22	M6	3 (2)
STOPFA3031	30	31	M6	7 (5)
STOPFA3233	32	33	M6	7 (5)
STOPFA3839	38	39	M6	7 (5)
STOPFA3940	39	40	M6	7 (5)
STOPFA4547	45	47	M8	10 (7)
STOPFA5354	53	54	M8	10 (7)
STOPFA5456	54	56	M8	10 (7)
STOPFA5759	57	59	M8	10 (7)
STOPFA6668	66	68	M8	10 (7)
STOPFA7274	72	74	M8	10 (7)

**Table 30 – Heavy-Duty Hose Clamp (T-Bolt Style)**

King Seal Fastener Technology Part # KTB412 (97-105mm) HPN 6763438	60-90 in-lb (6.8-10 N-m)	
--	-----------------------------	---

## ***17.4 HYDRAULIC MOTORS – TORQUE FOR MOUNTING BOLTS***

**Table 31 – Torques for Hydraulic Motors Mounting Bolts**

Torque N-m (ft-lb) +/-tolerance value	
Bolt Size	Hagglungs Hydraulic Motors
M16	280 +/-15 (205 +/-11)
M20	540 +/-20 (400 +/-15)
M24	900 +/- 30 (665 +/-22)
Lubricant	Hydraulic Oil

## ***17.5 BOSCH REXROTH DBDS PRESSURE RELIEF VALVES***

**Table 32 – Bosh Rexroth DBDS Pressure Relief Valves**

Size	Maximum Tightening Torque * (+/- 5%)	
NG	N-m	ft-lb
6	80	59
10	150	110
20	300	221
30	500	369

\* The tightening torques are recommended values assuming a friction coefficient of 0.12 and the use of a torque wrench.

## 17.6 BLADDER ACCUMULATOR NECK ADAPTOR SPECIFICATIONS

**Table 33 – Bladder Accumulator Neck Adaptor Specifications**

Accumulator Size	Accumulator Port Size	Torque [N-m]	Torque [ft-lb]
10L	BSPP 2" (G 2")	339 N-m	250 ft-lb
20L	BSPP 2" (G 2")	339 N-m	250 ft-lb
32L	BSPP 2" (G 2")	339 N-m	250 ft-lb
50L/54L	BSPP 2" (G 2")	339 N-m	250 ft-lb
50L High Flow	BSPP 2 ½" (G 2 ½")	420 N-m	310 ft-lb

## 17.7 HYDAC OIL LEVEL SIGHT GAUGE

HPN 2841146 (Hydac Model # 3070285 FSK127-2.5/0/-/12)	M12 banjo bolts	8 ft-lb (+1, 0) 10 N-m (+2, 0)
--	-----------------	-----------------------------------

## 17.8 HYDAC PRESSURE TRANSDUCERS

HPN 7980938 (Hydac Model # 926910 Pressure transmitter HDA 4776-A-300-453)	40 N-m (+10%, -0)	30 ft-lb (+10%, -0)
HPN 9247632 (Hydac Model # 927321 Pressure transmitter HPT 1776-A-0300-453)	40 N-m (+10%, -0)	30 ft-lb (+10%, -0)

## 17.9 DANFOSS PRESSURE TRANSDUCER


HPN 6830141 Danfoss Part # 063G2021, MBS 1250, 300 bar	M12x1	33 ft-lb (45 N-m) (+10%, -0)
---	-------	---------------------------------

## 17.10 NUMATICS AIR VALVE ASSEMBLY TORQUE SPECIFICATIONS

The following torque specifications are recommended by the supplier and should be used unless otherwise specified. These specifications apply to Numatics 2012, 2035, ISO 1, ISO 2 & ISO 3 air valve assemblies.

### 17.10.1 TORQUE SPECIFICATIONS FOR NUMATICS 2012 & 2035 AIR VALVE ASSEMBLIES

**Figure 5 – Numatics 2012 & 2035 Air Valve Assemblies**




**Table 34 – Numatics 2012 & 2035 Air Valve Assemblies**

Fastener	Description	2012 Air Valve Assy		2035 Air Valve Assy	
		Torque		Torque	
		N-m	in-lb	N-m	in-lb
1	Valve to Manifold	0.9-1.1	8-10	2.5-2.8	22-25
2	Valve to Sandwich Plate	0.9-1.1	8-10	2.8-3.4	25-30
3	Sandwich Plate to Manifold	0.9-1.1	8-10	2.8-3.4	25-30
4	Blanking Plate to Manifold	1.4-1.7	12-15	2.8-3.4	25-30



## 17.10.2 TORQUE SPECIFICATIONS FOR NUMATICS ISO 1, 2 & 3 AIR VALVE ASSEMBLIES

**Figure 6 – Numatics ISO 1, 2 & 3 Air Valve Assemblies**



**Table 35 – Numatics ISO 1, 2 & 3 Air Valve Assemblies**

Fastener	Description	ISO 1, 2 & 3 Air Valve Assemblies	
		Torque	
		N-mm	in-lb
1	Valve to Manifold	3.6-4.3	32-38
2	Valve to Sandwich Plate	3.6-4.3	32-38
3	Sandwich Plate to Manifold	3.6-4.3	32-38
4	Blanking Plate to Manifold	3.6-4.3	32-38

## 17.11 *HYDAC MALE PRESSURE TEST POINT*

HPN 2638323 Hydac designation: 6003737 (9/16-18 UNF, 630 bar, 1620 series, O-ring/Form E)	Thread 9/16-18 UNF	25 ft-lb (35 N-m) (+10%, -0)
---	--------------------	---------------------------------

## 18 INTERNATIONAL STANDARDS TORQUE SPECIFICATIONS

The following torque values obtained from international standards are specified on the drawing when deviating from the Husky general torque standard.

### 18.1 ISO 6162:1994 - SPLIT FLANGE ASSEMBLIES

**Table 36 – Code 61 Split Flange Assemblies**

4 Bolt Split Flange Assemblies Code 61 (25 bar to 350 bar series)		
Bolt Size	Torque (+25% - 0) See Section 18.3	
	N-m	ft-lb
M8	25	18
M10	53	40
M12	95	70
M16	220	160
Lubricant	Lubriplate FGL-1 or Molykote G – rapid plus with MoS2	

**Table 37 – Code 62 Split Flange Assemblies**

4 Bolt Split Flange Assemblies Code 62 (400 bar series)		
Bolt Size	Torque (+25% - 0) See Section 18.3	
	N-m	ft-lb
M8	25	18
M10	53	40
M12	95	70
M14	150	110
M16	220	160
M20	390	290
Lubricant	Lubriplate FGL-1 or Molykote G – rapid plus with MoS2	

### 18.2 CAUTION

It is important that all screws be lightly torqued (e.g. from 1 to 2 FFFT) before applying the final recommended torque values to avoid breaking the flange halves during installation.

### 18.3 NOTES

- The recommended torque values are consistent with the HGT-50 general standard. Exception: M14 bolts (special size requiring a note on the drawing).
- The recommended torque values may be increased by 25% when flange head screws of property 12.9 screws are used with Unbrako Durlok-12.9 screws.

## 19 PET MOLD AND HOT RUNNER SPECIAL TORQUE SPECIFICATIONS

Following torque specifications must be applied accordingly to ensure proper installation.

## 19.1 CAM FOLLOWER TORQUE SPECIFICATIONS

Table 38 – CAM Follower Torque Specifications

CAM follower HPN	Component	Torque [N-m]	Torque [ft-lb]
1425388	Nut	22 N-m	16 ft-lb
1502548	Nut	87 N-m	64 ft-lb
2739013	Cam Follower	87 N-m	64 ft-lb
	Set Screw	8.5-9 N-m	6.3-6.6 ft-lb
5792862	Cam Follower	87 N-m	64 ft-lb
	Set Screw	8.5-9 N-m	6.3-6.6 ft-lb

## 19.2 EOAT TUBE RETAINER PIN TORQUE SPECIFICATION

Figure 7 – EOAT Tube Retainer Pin Torque Specification




Table 39 – EOAT Tube Retainer Pin Torque Specification

Hex Size (mm)	Torque (N-m)	Torque (ft-lb)
5	37	27
4	20	15

## 19.3 COOLPIK VACUUM/BLOW PIN TORQUE SPECIFICATIONS


Table 40 – COOLPIK Vacuum/Blow Pin Torque Specifications

Vacuum/Blow Pin Size	Torque	
	N-m	ft-lb
M6	2	1.4
M12	15	11
M16	34	25
M20	60	44

## 19.4 COOLPIK MOVING PUCK INSTALLATION TORQUE SPECIFICATION

Apply following torque during moving puck installation.

**Figure 8 – Moving Puck Assembly Installation Torque Specification**




Torque the sub-assembly into the COOLPIK plate to 18 N-m through the top of the pin using an 8mm socket.

## 19.5 COOLPIK PLATE MOUNTING TORQUE SPECIFICATION

Apply HGT-80 [77N-m (56.8 lb-ft)] torque for M10 COOLPIK plate mounting screws.

**Figure 9 – COOLPIK Assembly on Machine Plenum**



## 19.6 MOLD/HOT RUNNER LIFT BARS MOUNTING SCREWS TORQUE APPLICATIONS

**Table 41 – Mold/Hot Runner Lift Bars Mounting Screws Torque Specifications**

Application		Hardware		Base/Threaded Material	Torque Standard
Mechanical	• Hot Runner/Mold Lift Bars Mounting Screws (Excluding M30 and Larger Sizes)	Screws and Threaded Rods	- DIN 912-12.9 SHCS - DURLOK-12.9-UNB HHS - DIN 933 & 931-10.9 HHCS - DIN 976-12.9&10.9 ROD - ASTM A574 SHCS	Steel Cast Iron	HGT-50
	• Hot Runner/Mold Lift Bars Mounting Screws, M30 and Larger Sizes	Screws and Threaded Rods	- DIN 912-12.9 SHCS - DURLOK-12.9-UNB HHS - DIN 933 & 931-10.9 HHCS - DIN 976-12.9&10.9 ROD - DIN 7991-10.9 FHCS - ISO 7380-10.9 BHCS - ASTM A574 SHCS	Any Material for Lift Bar Mounting Screws	HGT-35

## 19.7 GIB/WEAR PLATE MOUNTING SCREWS TORQUE SPECIFICATION

Apply HGT-50 on Gibs and Wear Plates.

Apply HGT-LHCS for Wear Plates using LHCS.

## 19.8 NECK RING PLUGS TORQUE SPECIFICATION

Apply appropriate torque to the Neck Ring plugs according to the table below.

**Table 42 – Neck Ring Plugs Torque Specifications**

HPN	Size	Material	Maximum Tightening Torque (+ 10% / - 10%)	
			N-m	ft-lb
4125714	M5	Brass	1.5	1.1
6359476	1/16	Brass	7	5.2

## 19.9 STACK INSERTS TORQUE SPECIFICATION

Apply HGT-80 on all SHCS's that are used on Stack Inserts.

## 19.10 TORQUE SPECIFICATION FOR WATER MANIFOLDS TO SLIDES

Apply HGT-80 on all SHCS's that are used to mount Slide Water Manifolds to Slides.

## 19.11 TORQUE SPECIFICATION FOR SLIDE TO CONNECTING BARS


Apply HGT-80 on all SHCS's that are used to mount Slides to Connecting Bars.

## 19.12 TORQUE SPECIFICATION FOR EOAT ASSY. TO ROBOT

Apply HGT-80 on all SHCS's that are used to mount EOAT Assembly to Robot Carriage.

## 19.13 TORQUE SPECIFICATION FOR NEXPET CORE SLEEVE SET SCREWS

**Figure 10 – Torque Specification for NexPET Core Sleeve Set Screws**



\*Apply LOCTITE® 222 or equivalent to the set screws and tighten them to 3N-m [2.2 lb-ft] – refer to NexPET mold manual for detailed installation instructions.

## 20 APPENDIX



<b>HUSKY</b>	<b>HS 252 - STANDARD ASSEMBLY TORQUES</b>		Page	37 of 49
	<b>Revision Level - 72 - PUBLISHED</b>	<b>Security Level - PUBLIC</b>	Standard No.	HS 252

## ***20.1 DLO DEVICE DETAILS (2205)***

Refer to the following sheets (See 6 to 17) for DLO device torque values.

**3VA Breakers**

BREAKERS		BREAKER LUGS			MOUNTING BOLTS		UNINSULATED FERRULES					FLEXIBLE BUSBAR				COMPRESSION LUGS / BUSBAR											
Type	SIZE (A)	Type	HPN	# of Conn.	Torque l-b-in N-m		AWG	Strip (mm)	AWG	Torque l-b-in N-m		Max Width (mm)	Thickness (mm)	Torque l-b-in N-m		Max W x D (mm)	Bolt Size	Torque l-b-in N-m									
3VA51	15-125	3VA9133-0JA11	10915876	1	N/A		14 - 1/0	12	14 - 6	44	5	13	1 - 7.2	71	8	N/A											
		3VA9134-0JA11	10973718						4 - 1/0	71	8																
		3VA9133-0JF60	10915905	2	71	8	14 - 4	12	14 - 8	53	6	N/A															
		3VA9134-0JF60	10973732						24	6 - 4	62									7							
				39																							
		3VA9133-0QA00	10915899	1	N/A		N/A						N/A							17 x 6.5	M6	71	8				
3VA9134-0QA00	10973740																										
		3VA9133-0QB00	10915916	1	71	8	N/A						N/A				22 x 8	M6	71	8							
		3VA9134-0QB00	10973748																								
3VA52	70-250	3VA9233-0JA11	10943437	1	N/A		10 - 3/0	19	10 - 4	53	6	20	1 - 6	89	10	N/A											
		3VA9234-0JA11	10973757						2 - 3/0	89	10																
		3VA9233-0JA12	10943456	1	N/A		4 - 313	20	4 - 2	71	8	20	3.2 - 6	106	12												
		3VA9234-0JA12	10973768						1 - 313	142	16																
		3VA9233-0JF60	10915946	2	177	20	14 - 4	15	14 - 8	53	6	N/A															
		3VA9234-0JF60	10973778					26	6 - 4	62	7																
				39																							
				3VA9233-0JJ22	10915940	1	177	20	4 - 4/0	25	4 - 4/0	275	31	N/A													
				3VA9234-0JJ22	10973780					50																	
				3VA9233-0QA00	10915935	1	N/A		N/A						N/A				25 x 8	M8	177	20					
		3VA9234-0QA00	10973788																								
		3VA9273-0QB00	10915949	2	133	15	N/A						N/A				32 x 10	M10	133	15							
		3VA9274-0QB00	10973803																								
3VA53	300-400	3VA9473-0JA13	11002426	1	N/A		2 - 373	26	2 - 3/0	142	16	24	2 - 10	248	28	N/A											
		3VA9474-0JA13	11039865						4/0 - 373	248	28																
		3VA9473-0JJ23	11002455	1	355	40	2/0 - 373	31	2/0 - 373	450	51	N/A															
		3VA9474-0JJ23	11039876					58																			
		3VA9373-0JF60	10973808	3	355	40	14 - 4	18	14 - 8	53	6	N/A															
		3VA9374-0JF60	10973814					35	6 - 4	62	7																
		3VA9473-0QA00	11002457	1	N/A		N/A						N/A				35 x 10	M10	355	40							
		3VA9474-0QA00	11039884																								
3VA54	450-600	3VA9473-0QB00	11002463	2	355	40	N/A						N/A				40 x 12.5	M10	177	20							
		3VA9474-0QB00	11039906																								
3VA55	600-800	3VA9573-0JB23	11039991	2	275	31	4/0 - 373	26	4/0 - 373	375	42.5	N/A				N/A											
		3VA9574-0JB23	11040004																								
		3VA9673-0JB32	11050762	3	275	31	4/0 - 262	26	4/0 - 262	225	25.5																
		3VA9674-0JB32	11050778																								
		3VA9673-0JJ43	11050763	2	375	42.5	4/0 - 373	23	4/0 - 373	325	36.5									N/A							
		3VA9674-0JJ43	11050780					45																			
		3VA9673-0QA00	11050770	1	N/A		N/A						N/A				50 x 10	M10 x1	275	31							
		3VA9674-0QA00	11050771																								

⊕

### BUSBAR MOUNTING ADAPTORS

Manufacturer	Part #	HPN	# of Conn.		Torque			Torque	
					lb-in	N-m		lb-in	N-m
Wohner	32981	6077583	1	MOUNTING BOLTS	1.8	0.2	LINE SIDE TUBES	Preinstalled 4 AWG wire leads	
Siemens	8US1213-4AP03	10915871	1		71	8		89	10
	8US1313-4AH03	10943617	1		106	12		177	20
	8US1213-4AH04	10943611	1						
	8US1313-4AM04	11039967	1						

### BUSBAR CONNECTION ADAPTORS

Manufacturer	Part #	HPN	# of Conn.	AWG	Max Busbar (mm)	Strip (mm)	Torque	
							lb-in	N-m
Wohner	01069	6251136	1	N/A	30 x 10	35	133	15
	01538	5960823	1	N/A	30 x 10	45	266	30
	01147	7861105	1	3/0 - 373	N/A	45	266	30
	01240	6679232	1	10 - 2/0	N/A	25	80	9
	01243	6257177	1	6 - 4/0	N/A	25	120	13.5
	32146	8010682	2	12 - 6	N/A	15	27	3

**DISTRIBUTION BLOCKS**

Manufacturer	Part #	HPN	POSITION	# of Conn.	AWG	Strip (mm)	AWG	Torque lb-in	N-m
Cooper Bussman	PDBFS303	6770277	Line / Load	1	4 - 313	32	4 - 313	275	31
	PDBFS330	5626032	Line	1	4 - 373	32	4 - 373	500	56.5
			Load	Row 1	3	30	6 - 4	45	5
				Row 2	3	15	8	40	4.5
							14 - 10	35	4
	PDBFS377	6197174	Line	2	4 - 262	30	4 - 262	275	31
			Load	Row 1	4	32	6	35	4
				Row 2	4	26	8	25	2.8
				Row 3	4	15	14 - 10	20	2.3
	PDBFS500	7500450	Line / Load	2	4 - 313	32	4 - 313	275	31
	PDBFS504	7500471	Line / Load	2	4 - 373	32	4 - 373	500	56.5
	16371-1 16371-3	5002820 2246870	Line	1	4 - 313	25	4 - 313	275	31
			Load	Row 1	3	25	* 14 - 2	120	13.5
				Row 2	3	16	6 - 4	45	5
				Row 3	3	12	8	40	4.5
							14 - 10	35	4
	16377-2 16377-3	4162385 4155603	Line	Row 1	1	25	4 - 4/0	275	31
			Load	Row 2	1	32	4 - 4/0	275	31
				Row 1	4	25	6	35	4
				Row 2	4	16	8	25	2.8
				Row 3	4	12	14 - 10	20	2.3
	16528-1 16528-3	3007511 2466523	Line	2	2 - 373	45	2 - 373	500	56.5
			Load	Row 1	2	32	* 6 - 2/0	120	13.5
				2	14 - 6	32	6	35	4
				2	6 - 2/0	16	8	25	2.8
				2	14 - 6	16	14 - 10	20	2.3

\* Larger termination screws

**DISTRIBUTION BLOCKS**

Manufacturer	Part #	HPN	POSITION	# of Conn.	AWG	Strip (mm)	AWG	Torque lb-in	N-m
Weidmueller	10 285 000 000 7942923		Line	1	M10	N/A	N/A	133	15
			Load	1					
Marathon	1333975CH 8235602		Line	1	2 - 373	40	6 - 373	375	42.4
			Load	Row 1	2	32	6 - 1	120	13.5
				Row 2	2	16	8	40	4.5
							14 - 10	35	4
Ferraz Shawmut	63131	7147588	Line	1	14 - 1/0	17	6 - 1/0	120	13.5
			Load	Row 1	2	22	14 - 8	50	5.6
				Row 2	2	10	6	35	4
							8	25	2.8
							10 - 14	20	2.3

Refer to HS 252 for Mechanical Torque specifications

# CONTACTORS

					Ferrules		FLEXIBLE BUSBAR		LUGS / BUSBAR			
Manufacturer	Size	Part #	HPN	# of Conn.	AWG	Strip (mm)	Max Width (mm)	Thickness (mm)	Max Width (mm)	Bolt Size	Torque l-b-in	N-m
Siemens	S2 3RT203	BOX LUGS ATTACHED		1	18 - 2	13	N/A		N/A		35	4
				2	18 - 4							
	S3 3RT204	BOX LUGS ATTACHED		1	14 - 1	17	9	2.4 - 4.8	N/A	44	5	
				2	14 - 2							
	S6 3RT105	WITHOUT BOX LUGS			N/A		N/A		15	M6	97	11
		3RT1955-4G	2600404	1	6 - 2/0	20	15.5	2.4 - 4.8	N/A			
				2	6 - 1/0							
		3RT1956-4G	2600407	1	6 - 262	20	15.5	2.4 - 8	N/A			
	2			6 - 3/0								
	S10 3RT106	WITHOUT BOX LUGS			N/A		N/A		17	M8	177	20
		3RT1966-4G	2600408	1	3/0-373	27	24	4.8 - 10	N/A			
	2			2/0-373								
S12 3RT107	WITHOUT BOX LUGS			N/A		N/A		25	M10	177	20	
	3RT1966-4G	2600408	1	3/0-373	27	24	4.8 - 10	N/A				
			2	2/0-373								

WIRE GAGE	
AWG	mm <sup>2</sup>
26	0.14
24	0.25
22	0.34
20	0.5
19	0.75
18	1.0
16	1.5
14	2.5
12	4
10	6
8	10
6	16
4	25
2	35
1	50

# OVERLOAD RELAYS

					Ferrules		LUGS / BUSBAR			
Manufacturer	Size	Part #	HPN	# of Conn.	AWG	Strip (mm)	Max Width (mm)	Bolt Size	Torque b-in	N-m
Siemens	S2 3RU213	BOX LUGS ATTACHED		1	18 - 2	13	N/A		35	4
				2	18 - 4					
	S3 3RU214	BOX LUGS ATTACHED		1	14 - 1	17	N/A		44	5
				2	14 - 2					
	S6 3RB205	RT1955-4G	2600404	1	6 - 2/0	20	N/A		97	11
				2	6 - 1/0					
		RT1956-4G	2600407	1	6 - 262	20	N/A			
				2	6 - 3/0					
		WITHOUT BOX LUGS			N/A		15	M8		
S10 3RB206	RT1966-4G	2600408	1	3/0 - 373	27	N/A		177	20	
			2	2/0 - 373						
			WITHOUT BOX LUGS			N/A				25

STUD SIZE	
USA	METRIC
#2	M2
#4	M2.5
#5	M3
#6	M3.5
#8	M4
#10	M5
1/4"	M6
5/16"	M8
3/8"	M10
7/16"	M11
1/2"	M12
5/8"	M16

Refer to HS 252 for Mechanical Torque specifications

## MOTOR STARTER PROTECTORS

					Ferrules		LUGS / BUSBAR			
Manufacturer	Size	Part #	HPN	# of Conn.	AWG	Strip (mm)	Max Width (mm)	Bolt Size	Torque l-b-in    N-m	
Siemens	S2 3RV203	BOX LUGS ATTACHED		1	18 - 2	13	N/A		35	4
				2	18 - 4					
	S3 3RV204 3RV274	BOX LUGS ATTACHED		1	14 - 1	17	N/A		44	5
				2	14 - 2					
		WITHOUT BOX LUGS			N/A		15	M6		

## MACHINE / MOLD HEATS

					Ferrules		LUGS / BUSBAR			
Manufacturer	Type	Part #	HPN	# of Conn.	AWG	Strip (mm)	Max Width (mm)	Bolt Size	Torque lb-in	N-m
Siemens	SSY4	(1,2,3)-Pole		2	14 - 4	15	N/A		27	3
	SITOP	6EP1437-3BA10 6EP4137-3AB00	8098974 7829488	2	14 - 6	12			11	1.2
Wohner	AES-CC	31298	4985144	1	14 - 8	11			20	2.3
		31299	4985089		6 - 4				25	2.8
	CTB-T35	31550	4985169	1	10 - 1/0	15			50	5.6
ABA	6 Slot	ICC3.2	7869129	1	N/A		15	M5	20	2.3

## PE CONNECTIONS

Manufacturer	Part #	HPN	# of Conn.	AWG	Strip (mm)	Bolt Size	Torque	
							l-b-in	N-m
Brumall	1024-R0	2172625	1	6 - 262	22	N/A	375	42.4
			24	8	10		40	4.5
				14 - 10			35	4
Hoffman	10 Hole PE busbar	2617195	8	N/A		M8	89	10
			2			M10	177	20
	6 Hole PE busbar	3086616	3	N/A		M8	89	10
			3			M10	177	20
	PE stud	N/A	1	N/A		M6	20	2.3

Refer to HS 252 for Mechanical Torque specifications



## LINE FILTERS

				POWER CONNECTIONS					PE CONNECTION		
Manufacturer	Part #	HPN	Size	max. AWG	Strip (mm)	Bolt Size	Torque l-b-in N-m		Bolt Size	Torque l-b-in N-m	
BAUMULLER (A211)	BFN 3-1-030-001	2351717	30A	8	9	N/A	9	1	M5	18	2
	BFN 3-1-042-001	2351719	42A								
	BFN 3-1-056-001	2351721	56A								
	BFN 3-1-075-001	2351722	75A	4	19		15	1.7	M6	35	4
	BFN 3-1-100-001	2351723	100A								
	BFN 3-1-130-001	2351724	130A								
	BFN 3-1-180-001	2351726	180A	3/0	27		62	7	M10	53	6
	BFN 3-1-250-001	4683445	250A								
	BFN 3-1-270-001	2620271	270A								
	BFN 3-1-320-101	4570913	320A	N/A		M10	142	16		142	16
	BFN 3-1-400-101	4684162	400A			M12					
	BFN 3-1-600-101	4684158	600A			M10					
SIEMENS (A211)	6SL3000-0BE21-6DA0	5157016	16kW	8	10	N/A	15	1.7	M6	53	6
	6SL3203-0BE31-1BA0	7375741	37kW	2	24	N/A	62	7	M10	89	10
	6SL3203-0BE32-5AA0	6884295	132kW	N/A		M10	221	25	N/A		

WIRE GAGE	
AWG	mm <sup>2</sup>
26	0.14
24	0.25
22	0.34
20	0.5
19	0.75
18	1.0
16	1.5
14	2.5
12	4
10	6
8	10
6	16
4	25
2	35
1	50

STUD SIZE	
USA	METRIC
#2	M2
#4	M2.5
#5	M3
#6	M3.5
#8	M4
#10	M5
1/4"	M6
5/16"	M8
3/8"	M10
7/16"	M11
1/2"	M12
5/8"	M16

Refer to HS 252 for Mechanical Torque specifications



## LINE REACTORS

				POWER CONNECTIONS				PE CONNECTION			
Manufacturer	Part #	HPN	Size	max. AWG	Strip (mm)	Bolt Size	Torque lb-in N-m		Bolt Size	Torque lb-in N-m	
BAUMULLER (A218)	BK3-0040/0050-002	6344019	40A	6	15	N/A	9	3	M6	53	6
	BK3-0065/0080-002	11005628	65A	4	18						
	BK3-0080/0100-002	11005647	80A	1	24		53	6			
	BK3-0115/0140-002	11005650	115A							106	12
	BK3-0065/0080-001	5831222	65A	N/A		M6	53	6	M6	53	6
	BK3-0080/0100-001	5831202	80A			M8	106	12			
	BK3-0115/0140-001	4922039	115A			M10	133	15		106	12
	BK3-0165/0200-001	4684155	165A								
	BK3-0195/0240-001	4921887	195A								
	BK3-0275/0340-001	4121316	275A								
	BK3-0365/0450-001	4420121	365A			M12	177	20			
	BK3-0450/0550-001	4922113	450A								
	BK3-0615/0750-001	4684150	615A								
SIEMENS (A194)	6SL3000-0DE21-6AA0	4858572	16 kW	6	14	N/A	11	1.2	Same as POWER CONNECTIONS		
	6SL3000-0DE23-6AA0	4858565	36 kW	2	19		22	2.5			
	6SL3000-0DE25-5AA1	3687230	55 kW	1/0	24		62	7			
	6SL3000-0DE28-0AA1	4858569	80 kW	4/0	35		SPRING CLAMP		M10	221	25
	6SL3000-0DE31-2AA1	4858567	120 kW								

WIRE GAGE	
AWG	mm <sup>2</sup>
26	0.14
24	0.25
22	0.34
20	0.5
19	0.75
18	1.0
16	1.5
14	2.5
12	4
10	6
8	10
6	16
4	25
2	35
1	50

STUD SIZE	
USA	METRIC
#2	M2
#4	M2.5
#5	M3
#6	M3.5
#8	M4
#10	M5
1/4"	M6
5/16"	M8
3/8"	M10
7/16"	M11
1/2"	M12
5/8"	M16

Refer to HS 252 for Mechanical Torque specifications





## ACTIVE INTERFACE MODULES

				POWER CONNECTIONS				PE CONNECTION			
Manufacturer	Part #	HPN	Size	max. AWG	Strip (mm)	Bolt Size	Torque		Bolt Size	Torque	
							l-b-in	N-m		l-b-in	N-m
SIEMENS (A195)	6SL3100-0BE21-6AB0	4959543	16 kW	6	14	N/A	15	1.7	M8	115	13
	6SL3100-0BE23-6AB0	5854353	36 kW	1/0	24		53	6			
	6SL3100-0BE25-5AB0	4021256	55 kW								
	6SL3100-0BE28-0AB0	4021251	80 kW	N/A		M8	115	13			
	6SL3100-0BE31-2AB0	4021250	120 kW								

WIRE GAGE	
AWG	mm <sup>2</sup>
26	0.14
24	0.25
22	0.34
20	0.5
19	0.75
18	1.0
16	1.5
14	2.5
12	4
10	6
8	10
6	16
4	25
2	35
1	50

## ACTIVE LINE MODULES

				POWER CONNECTIONS					PE CONNECTION			DC LINK BUSBAR	
Manufacturer	Part #	HPN	Size	max. AWG	Strip (mm)	Bolt Size	Torque l-b-in N-m		Bolt Size	Torque l-b-in N-m		Torque l-b-in N-m	
SIEMENS (A20)	6SL3130-7TE21-6AA4	4959545	16 kW	8	12	N/A	15	1.7	M5	27	3	15.9	1.8
	6SL3130-7TE23-6AA3	5682121	36 kW	N/A		M6	53	6	M6	53	6		
	6SL3130-7TE25-5AA3	5808068	55 kW			M8	115	13	M8	115	13		
	6SL3131-7TE25-5AA3	7260842											
	6SL3130-7TE28-0AA3	3890439											
	6SL3131-7TE28-0AA3	6849701											
	6SL3130-7TE31-2AA3	3869320	120 kW										
6SL3131-7TE31-2AA3	6849702												
	6SL3162-2BM01-0AA0	3869348	DC link	4/0	25	N/A	115	13	N/A				

STUD SIZE	
USA	METRIC
#2	M2
#4	M2.5
#5	M3
#6	M3.5
#8	M4
#10	M5
1/4"	M6
5/16"	M8
3/8"	M10
7/16"	M11
1/2"	M12
5/8"	M16

Refer to HS 252 for Mechanical Torque specifications



MACHINE MODEL  
UNIVERSAL MASTER

	Name	Date	Time
Edited	dieetwo	2/4/2022	11:10:58 AM
Appr			
Checked			
Original			

DESCRIPTION  
DLO DEVICE DETAILS

PROJECT	Sheet	Total
MACHINE	13	23
DRAWING NO.		
UNIVERSAL MASTER		



## SERVO DRIVES

				POWER CONNECTIONS					PE CONNECTION			DC LINK BUSBAR	
Manufacturer	Part #	HPN	Size	max. AWG	Strip (mm)	Bolt Size	Torque l-b-in N-m		Bolt Size	Torque l-b-in N-m		Torque l-b-in N-m	
BAUMULLER (209)	BM4434 BM4435	8425222 8425223	40A 60A	4	16	N/A	18	2	Same as POWER CONNECTIONS	N/A			
	BM4443	8425143	80A	1	24	N/A	62	7					
	BM4444	8098421	100A										
	BM4445	8098423	130A										
	BM4446	8098425	150A										
	BM4453	8098510	150A	N/A		M8	106	12					
	BM4454	8098511	210A										
	BM4462	8098635	250A			M10	133	15					
	BM4463	8098636	300A										
	BM4466	8098637	350A										
	BM4472	8098684	450A										
	BM4473	8098685	594A										
SIEMENS (A23) (A235) (A41, A42) (A55)	6SL3120-1TE24-5AA3 6SL3121-1TE24-5AA3	3869422 7260827	45 A	N/A		M6	53	6	M6	53	6	15.9	1.8
	6SL3120-1TE26-0AA3 6SL3121-1TE26-0AA3	4870136 6849696	60 A										
	6SL3120-1TE28-5AA3 6SL3121-1TE28-5AA3	4054901 6849698	85 A			M8	115	13		115	13		
	6SL3120-1TE31-3AA3 6SL3121-1TE31-3AA3	4054899 6849699	132 A					M8					
	6SL3120-1TE32-0AA4 6SL3121-1TE32-0AA4	3869421 6849700	200 A										
	6SL3210-1PE27-5UL0	7251771	37 kW	2	18	N/A	35	4	Same as POWER CONNECTIONS			N/A	
	6SL3210-1PE31-1UL0	7251769	55 kW	2/0	25	N/A	80	9					
	6SL3210-1PE31-8UL0	7162332	90 kW	N/A		M10	212	24					
	6SL3210-1PE32-5UL0	6852710	132 kW										

WIRE GAGE	
AWG	mm <sup>2</sup>
26	0.14
24	0.25
22	0.34
20	0.5
19	0.75
18	1.0
16	1.5
14	2.5
12	4
10	6
8	10
6	16
4	25
2	35
1	50

STUD SIZE	
USA	METRIC
#2	M2
#4	M2.5
#5	M3
#6	M3.5
#8	M4
#10	M5
1/4"	M6
5/16"	M8
3/8"	M10
7/16"	M11
1/2"	M12
5/8"	M16

Refer to HS 252 for Mechanical Torque specifications



SERVO MOTORS										
					POWER CONNECTIONS			PE CONNECTION		
Manufacturer	Part #	HPN	Motor Size	Terminal Box #	Bolt Size	Torque lb-in N-m		Bolt Size	Torque lb-in N-m	Cable Entry Ø
BAUMULLER	DS2-100LO54W-20-5	8008538	100	12	M8	53	6	Same as POWER CONNECTIONS	M40 x 1 M25 x 1	
	DS2-100KO54W-30-5	8008324								
	DS2-100MO54W-30-5	8008338								
	DS2-100BO54W-20-5	8008540 8135668		14					M63 x 1 M25 x 1	
	DS2-100LO54W-30-5	8008350								
	DS2-100BO54W-30-5	8008351 8012949								
	DS2-132MO54W-20-5	8025038	132	22	M10	89	10		M40 x 2 M25 x 1	
	DS2-132ML54W-30-5	8008355 8010220		24					M63 x 2 M25 x 1	
	DS2-132MO54W-30-5	8008356 8012948								
	DS2-132LO54W-30-5	8008354		26						
	DS2-132BO54W-30-5	8008353 8012942								
	DS2-160KO54W-30-5	8012944	160	32	M12	89	15.5		64 x 2 25.5 x 1	
	DS2-160MO54W-30-5	8008366 8012945		34					76 x 2 25.5 x 1	
	DS2-160LO54W-30-5	8008358 8012946								
	DS2-160BO54W-30-5	8008357 8012947								
DS2-200LO54W-27-5	8020273	200		46				M16	89	10
DS2-200MO54W-27-5	8020002									

WIRE GAGE	
AWG	mm <sup>2</sup>
26	0.14
24	0.25
22	0.34
20	0.5
19	0.75
18	1.0
16	1.5
14	2.5
12	4
10	6
8	10
6	16
4	25
2	35
1	50

STUD SIZE	
USA	METRIC
#2	M2
#4	M2.5
#5	M3
#6	M3.5
#8	M4
#10	M5
1/4"	M6
5/16"	M8
3/8"	M10
7/16"	M11
1/2"	M12
5/8"	M16

Refer to HS 252 for Mechanical Torque specifications



MACHINE MODEL  
**UNIVERSAL MASTER**

	Name	Date	Time
Edited	dieetwo	2/4/2022	11:56:50 AM
Appr			
Checked			
Original			

DESCRIPTION  
**DLO DEVICE DETAILS**

PROJECT	Sheet	Total
MACHINE	15	23
DRAWING NO. <b>UNIVERSAL MASTER</b>		



## PUMP MOTORS

[Data Sheets](#)

			POWER CONNECTIONS				PE CONNECTION					
Manufacturer	HP	# of Conn.	AWG	Strip (mm)	Bolt Size	Torque l-b-in N-m		AWG	Strip (mm)	Torque l-b-in N-m		Cable Entry Ø
EMOD	20 - 60	6	N/A		M8	53	6	10 - 1/0	20	71	8	Pg13 x 7 Pg11 x 2
	60 - 100											Pg16 x 7 Pg11 x 2
	100 - 125	6			M10	89	10	1 - 3/73				Pg21 x 7 Pg11 x 2
	125 - 150	6			M12	137	15.5					
	200 - 250	6	4 - 4/0	35	N/A	Cage Clamp *	Same as POWER CONNECTIONS				M40 x 7 M20 x 1	
	200 - 600	12									M32 x 13 M20 x 1	

\* WAGO TYPE 285-195 -> USE BARE DLO (NO STOPPER)

WIRE GAGE	
AWG	mm <sup>2</sup>
26	0.14
24	0.25
22	0.34
20	0.5
19	0.75
18	1.0
16	1.5
14	2.5
12	4
10	6
8	10
6	16
4	25
2	35
1	50

STUD SIZE	
USA	METRIC
#2	M2
#4	M2.5
#5	M3
#6	M3.5
#8	M4
#10	M5
1/4"	M6
5/16"	M8
3/8"	M10
7/16"	M11
1/2"	M12
5/8"	M16

Refer to HS 252 for Mechanical Torque specifications



MACHINE MODEL  
**UNIVERSAL MASTER**

	Name	Date	Time
Edited	dleeTwo	2/4/2022	11:56:50 AM
Appr			
Checked			
Original			

DESCRIPTION  
**DLO DEVICE DETAILS**

PROJECT	WIRE	+
MACHINE		
DRAWING NO.	Sheet <b>16</b>	Total <b>23</b>
UNIVERSAL MASTER		

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19

**CLASS A --> Electrical threaded connections (>30A)**

#	Connection Type
1	DLO Conductors
2	Non DLO Conductors (>=8AWG)
3	Flexible Busbars
4	Busbar Connection / Mounting Adaptors
5	Comb-Type Busbars
6	SINAMICS DC Link busbars
7	Main Breaker Lug Mounting Bolts

**CLASS A NOTES:**

All Class A connections shall use Torque Record Report

**CLASS A TORQUE RECORD REPORT**

Lookup torque values must be predefined prior to assembly  
Operator to record name for each torqued connection point  
Inspector to record name for each verification point  
This report is a CTQ supplier deliverable  
This report will be available for post build reference  
Refer to SWI-2551

**CLASS B --> Electrical threaded connections (<=30A)**

#	Connection Type
1	Non DLO Conductors (<=10AWG)
2	Distribution Blocks (load side)
3	SSY Circuit Breakers
4	AES-OC Fuse holders
5	Control Transformers *
6	DC power supplies *
7	Buffer Module *
8	RV surge suppressors *
9	Outlets *
10	Control Relays *
11	Heat Exchangers *
12	Grounding Studs
13	Bonding Straps

**CLASS B NOTES:**

All Class B connections shall be tightened and tug tested

\* Future design change to spring cage terminals

**CLASS C --> Device Mounting**

#	Mounting Type
1	Busbar supports
2	Busbar Adaptors
3	Breakers
4	Breaker Handles
5	Distribution Blocks
6	Contactors
7	Line Filters
8	Line Reactors
9	Servo Drives
10	Heat Sink
11	Solid State Relays
12	Aluminum Components
13	IPC / Battery
14	Din Rail
15	Wire Duct
16	Connector bulkheads / hoods
17	Strain Relieves / Gland Plates
18	Enclosure - Accessories
19	Adaptor plates
20	Current Transformers

**Torque value reference:**

1. Husky DLO Tables
2. HS252
3. Specials -> OEM installation guide